# Market Perspective Trends and Timing

Transformations in Lighting 2008 DOE Solid-State Lighting R&D Workshop

January 29, 2008

Vrinda Bhandarkar

Strategies Unlimited





### **Outline**

- □ Introduction
- Markets
- Lighting
- Outlook






### **HB LED Market Analysis**

- Market is worldwide in scope
  - -Main production and consumption are in US, Europe, Japan, Taiwan, S. Korea, China, SE Asia
- Market analyzed in terms of packaged devices (lamps, SMDs, multichip, high-power packages)
- Materials include InGaAIP (red-orange-yellow) and InGaN (blue, blue-green, green, white)
   -Higher performance, "qualified" devices
- Market segmented and sub-segmented by applications that have similar functionality





### **HB LED Application Segments**



### **Outline**

- Introduction
- □ Markets
- Applications
- Lighting
- Outlook






#### **HB LED Market Trends**

- Market continued its "slow growth" phase in 2006similar patterns to 2005
- Overall market growth was 6% to \$4.2 billion
- Heavily influenced by ongoing decline in mobile phone market
- Other applications continued to have attractive growth rates
- □ Substantial ASP erosion across many product types






### Recent Market History








### Market Growth Without Mobile Phones








### 2006 Market by Application








### 2006 Market by Color







#### **HB LED Units and ASPs**







### **Outline**

- Introduction
- Markets
- □ Lighting
- Outlook





### Lighting10 Significant Near-Medium Term Applications

- Architectural
- Channel letter/ contour lighting
- Consumer portable (e.g. flashlights)
- Residential
- Machine vision

- Retail display
- Entertainment
- Safety/Security
- Outdoor area
- Off-grid (generally solar-powered)





### Market for HB LEDs in Lighting

- □ The 2006 market for HB LEDs used in lighting was \$205 million
- □ Growing at around 37% per year the highest of any HB LED application
- □ Projected to reach ~\$1 billion in 2011
- Majority of applications use RGB today, but white will increase to more than 60% of the market by 2011





#### **SSL Market Drivers**

- Visual appeal
  - Saturated colors, near point source of light, design flexibility
- Long lifetime
  - Applications with high maintenance costs
- Compact form factor
- Lack of radiated heat
- Low-voltage operation
- Energy efficiency
  - Colors, low wattage applications (e.g. battery and solar powered), low temperature operation






### Solid-State Lighting Market

- ☐ The market is highly fragmented, encompassing many niche applications
  - Architectural lighting is the largest
  - Most applications are for colored (R,G,B) light
  - General illumination applications are starting to emerge
- ☐ Hundreds of companies worldwide are participating at the luminaire or fixture level
  - Strategies Unlimited has identified and described approximately 300 such companies, but there are more
  - Participants range from start-ups to the world's largest lighting companies





### Structure of the Lighting Fixture Industry







### Status of SSL Fixture Industry

- Many small companies dedicated to SSL; high level of LED expertise
- Many large and medium lighting companies, with some interest in SSL, offer a few products
  - Most lack in-house LED expertise
  - Rely on outside consultants for design, prototyping
- Volumes are small and costs are high, independent of high cost of LEDs
- Products in the market are highly variable in terms of quality





### **SSL Market Development**

- Most product and market development is being carried out by small, specialized companies
  - With a few exceptions, e.g. Philips Lighting, Zumtobel
- Generally, large lighting fixture company interest ranges from zero to modest (but interest is growing)
  - In-house LED expertise is minimal
  - European companies moving faster than US
- Large companies control the access to sales and distribution channels and customers






### Refrigerated Display Case Success Story

- Wal-Mart adoption of LED refrigerated display case lighting from GELcore was the SSL "story of the year"
- Installing in all new Sam's Club and SuperStores from Dec.
   2006, approximately 175 new stores in 2007 in US
  - Part of the Wal-Mart's "green" strategy
- Drivers are energy and maintenance savings
  - Can use occupancy sensors to turn off lighting during low traffic periods (impossible with fluorescent due to slow startup)
- Other supermarket chains are likely to follow Wal-Mart's lead





## Linear Fluorescent vs. White LED Relative Efficiency







### **Retail Display Lighting**

- White LEDs are being used to provide attributes that are advantageous for certain types of products:
  - High-end retail (e.g. designer label branded stores)
    - "High-tech" look; interesting effects; design flexibility
  - Cosmetics
    - □ Lack of radiated heat from source
  - Jewelry
    - Sparkling appearance from point light source; compact; long life
  - Refrigerated display cases
    - ☐ More efficient than linear fluorescents at low temperatures; rapid start-up; long lifetime





### Retail Display Lighting Examples



Source: Hera GmbH





Source: Nualight

Source: MAG-LED





### LED lighting fixtures – a wide variety in the market





### LED Lighting Fixtures (I)





Source: Altman

Source: Lighting Services Inc./
TIR Systems (now Philips)





### LED Lighting Fixtures (2)





Source: ERCO Source: Hera GmbH





### LED Lighting Fixtures (3)



Source: Lucesco



Source: Herman Miller/Fuseproject





### LED Lighting Fixtures (4)



Source: Elletrica Rotaliana srl



Source: Progress Lighting






### LED Lighting Fixtures (5)



Source: beta LED



LED lanterns presented to the focus group and interview participants for evaluation for the Lumina Project





### LED Lighting Fixtures (6)

#### **Solar Powered**



Source: Bronzlite



Source: Advanced LEDs





### LED Lighting Fixtures (7)



Philips Solid
State Lighting-Color Kinetics



**GE Luminations' Channel Letters** 







### **Opportunities for SSL**

- Offer a unique lighting solution
- Create an aesthetically pleasing lighting environment
- □ Deliver value (on a cost-of-ownership basis)
- Provide lighting products adapted to unique physical environments
- □ Save energy; comply with regulatory requirements (e.g. Title 24 in California)





### Challenges for SSL

- ☐ High initial cost
- Other alternatives for energy efficiency
- Consistency of color/binning issues
- Need to provide a complete lighting solution with ease of installation
- Adapt to standard electrical interfaces and controls
- □ Realistic claims of performance
- Development of standards
- Need widespread base of lighting fixture designers and engineers who understand LEDs
- □ Need for high-efficiency light engine/fixture design





### **Outline**

- Introduction
- Markets
- Lighting
- □ Outlook






# How long will it take for the commercialization of SSL? --Are we there yet?






### Global Light Production by Lamp Type in 2005








## **CFL Adoption**







## Estimated Global CFL Sales by Region 1990-2004




Source: IEA (2006)






#### **CFLs Performance**








## North American Red Traffic Signal Market Penetration - Percent of Installed Base







# Evolution of White LED Luminous Efficacy (Best Commercial Products)







## State-of-the-Art White LED Performance\* – Laboratory

- Small chip (~350 micron square; 20 mA drive current)
  - Nichia 150 lm/W
  - Cree I31 lm/W
- Large chip (≥ Imm square; 350 mA drive current)
  - Cree 129 lm/W
  - Lumileds I I 5 lm/W

\*Cool white (CCT ≥4500 K)





## State-of-the-Art White LED Performance\* – Commercial

- Small chip
  - Nichia 96 lm/W
- Large chip
  - Cree 93 lm/W
  - Lumileds 91 lm/W
  - Seoul Semiconductor 88 lm/W

\*Cool white, highest performance bins





## Performance of Warm White LEDs

- Many general illumination applications require a warm white color, similar to that of incandescent lamps
- Using the appropriate phosphor mix, a variety of warm white (CCT = 2700-3500K) colors can be achieved
- □ However, in all cases, the efficacies of warm white LEDs are much less than those of cool white LEDs





## Comparison of "Best of Class" Commercial White LED (Large Chip) Luminous Efficacies

Company	Cool White Efficacy (Im/W)	Warm White Efficacy (lm/W)
Cree	93	54
Philips Lumileds	91	54
Seoul Semiconductor	88	55
Nichia	70	61





## What is the Competition?







Incandescent R30 \$7 770 lm/75 W 2,000 hrs


CFL R30 \$10 715 lm/16 W 10,000 hrs LED R30 \$90 420-500 lm/15 watts 50,0000 hrs





### **Incandescent Lamp**








Lamp

Socket





#### **CFL= Lamp + Ballast**










## SSL(Lamp Replacements) LEDs + Power Supply (driver) +Thermal Management






http://www.wedlake.pwp.blueyonder.co.uk/images/led lights/inside reg.JPG





## SSL (Lamp Replacements) LEDs + Power Supply (driver) + Thermal Management




Source: Maxim
Integrated heatsink (left) of the white-LED MR16 lamp and
the compact LED driver circuit (center, Maxim MAX 16820 IC circuit)
which is situated within the lamp housing (right)






#### **Efficacy Comparison of Light Sources for General Lighting**








#### **Test Results of Fixtures Tested by DOE**








### **Annual Cost of Lighting (Today)**







### **Annual Cost of Lighting (Future)**







## **Essential Design Principles for LED Light Engines**

- I. Don't waste electrons
- 2. Don't waste photons
- 3. Be cool!





### **Examples**

#### **Efficient Design**

Start with 70 lm/W I-W white LEDs (at 25 °C junction temperature) Assume: 90% electrical efficiency; 90% optical efficiency; operate at 65 °C junction temperature

Light engine efficacy =  $70 \times 0.9 \times 0.9 \times 0.85 = 48 \text{ Im/W}$ 

#### **Inefficient Design**


Start with 70 lm/W I-W white LEDs (at 25 °C junction temperature) Assume: 80% electrical efficiency; 80% optical efficiency; operate at 100 °C junction temperature

Light engine efficacy =  $70 \times 0.8 \times 0.8 \times 0.75 = 34 \text{ Im/W}$ 





## What 50,000 Hours Means in Practical Terms







#### **Outline**

- Introduction
- Markets
- Lighting
- □ Outlook






### **LED Lighting Market Outlook**

- □ Niche lighting applications will continue to grow
- General illumination (e.g. white light applications)
   will become increasingly important
- Presumes continuing improvement in white LED price/performance
  - And luminaire performance!
- Presumes substantial marketing efforts to penetrate the conventional lighting market
  - Penetration will proceed gradually application by application
- □ Overall forecast 37% CAGR to ~\$1 billion in 2011





#### Forecast for LEDs in Lighting Market







### Thank you!



